



ANTIFOAM 29

ANTIFOAM 29 is a non-silicone chemical suspension for use as an antifoaming/de-foaming agent in aqueous systems of soluble oils, semi-synthetics, synthetics, cleaners, high water based hydraulic fluids, and water glycol hydraulic fluids. **ANTIFOAM 29** is completely water dispersible and does not adhere to metal surfaces. Subsequent finishing operations, such as painting or plating will not be impaired by its use.

USAGE

ANTIFOAM 29 is used at a rate of 3 to 4 ounces per 100 gallons of fluid. **ANTIFOAM 29** should be introduced slowly to the inlet side of the recirculation pump to achieve its most efficient dispersion throughout the system.

PHYSICAL CHARACTERISTICS

Density	1.06 g/ml
Appearance	Translucent White Liquid
pH	7.5 to 8.5

BENEFITS

- **Is a Highly Effective Antifoam Solution**
- **Is Compatible With a Wide Range Coolants and Cleaners**
- **Does Not Adhere To Metal Surfaces**
- **Will Not Impair Subsequent Painting or Plating Operations**

TECHNICAL SUPPORT

This is a Proprietary product. TOWER wants to assist you in evaluation and selection of suitable products. We urge you to take advantage of this service. This information sheet and TOWER's assistance, however, are not a substitute for your own testing and evaluation.