



TOWERDRAW 9510-TD

TOWERDRAW 9510-TD is a petroleum-based product formulated for heavy-duty metal forming operations. It has unique wetting properties in combination with sulfur chlorinated extreme pressure additives. The chemistry of **TOWERDRAW 9510-TD** is suitable for tough stainless steel forming operations and for use on high strength ferrous metals. **TOWERDRAW 9510-TD** is designed for high speed stamping, transfer press operations and other multi-stage forming, drawing and deep drawing applications.

USAGE

TOWERDRAW 9510-TD should be used as supplied from the drum. **TOWERDRAW 9510-TD** can be applied in minimal amounts through airless spray, drip, roller coater, or in recirculating systems.

PHYSICAL CHARACTERISTICS

Density	1.01 g/ml 8.40 lbs./gal.
Appearance	Clear Amber Liquid
Odor	Bland Petroleum Odor
Viscosity	160 SUS @ 100°F (typical)

BENEFITS

- **Contains No Hazardous Ingredients**
- **Provides Excellent In-Process Rust Protection**
- **Cleans Easily in Aqueous Cleaners**
- **Designed for Heavy Duty Operations**
- **Exhibits Excellent Surface Wetting & Anti-Galling Characteristics**
- **Offers Low Odor Characteristics at High Temperatures**
- **Receives Excellent Operator Acceptance**

TECHNICAL SUPPORT

TOWER wants to assist you in evaluation and selection of suitable products. We urge you to take advantage of this service. This information sheet and TOWER assistance, however, are not a substitute for your own testing and evaluation. 02135