



## QUADROIL HP-6

**QUADROIL HP-6** is a premium quality anti-wear hydraulic fluid. **QUADROIL HP-6** is formulated with a blend of high quality base oils and a superior additive system. It is designed to provide high levels of anti-wear protection, oxidation stability, long filter life, and anti-foam characteristics.

### PHYSICAL CHARACTERISTICS

| <u>DESCRIPTION</u>                           | <u>TYPICAL RESULTS</u> |
|--|------------------------|
| ISO Grade                                    | 100                    |
| Specific Gravity                             | 0.88                   |
| Viscosity @ 100° F., S.U.S.                  | 580                    |
| Viscosity @ 210° F., S.U.S.                  | 66                     |
| Viscosity Index                              | 95                     |
| Flash Point ° F.                             | >500                   |
| Pour Point ° F.                              | 21                     |
| ATSM D943 Oxidation Test<br>Hours to 2.0 NNA | 2,600+                 |
| ATSM D655 Rust Test                          | Pass                   |
| ASTM D130 Copper<br>Strip Corrosion          | 1A                     |

### TECHNICAL SUPPORT

**TOWER** wants to assist you in evaluation and selection of suitable products. We urge you to take advantage of this service. This information sheet and **TOWER's** assistance, however, are not a substitute for your own testing and evaluation. 06101