

SAFETY DATA SHEET (SDS)

1 - IDENTIFICATION

TOWERPRO 5212-B

Chemical family: Emulsifiable Mineral Oil

Recommended use: Metalforming Lubricant

Tower Metalworking Fluids

4300 South Tripp Ave. Chicago, IL 60632

Information telephone #: (773) 927-6161 (7:30 AM to 4 PM, CST, Monday to Friday)

24 Hr. emergency telephone #: CHEMTREC: (800) 424-9300

2 - HAZARDS IDENTIFICATION

Classification of chemical:

This material is classified as non-hazardous under OSHA regulations (29CFR 1910.1200) (Hazcom 2012).

Signal word: None required.

Hazard Pictogram: None required.

Hazard statement: None required.

Precautionary statement: None required.

3 - COMPOSITION/ INFORMATION ON INGREDIENTS

Chemical name	CAS#	Concentration
Ingredients classified as non-hazardous under OSHA regulations (29CFR 1900-1200) (Hazcom 2012)		

4 - FIRST-AID MEASURES

Description of first aid measures:

Inhalation: If overcome by fumes from hot product, move to fresh air. Get medical attention.

Ingestion: Do not induce vomiting. Get immediate medical attention.

Skin: Wash with warm water and mild soap. Remove contaminated clothing. Launder or dry-clean soiled clothing before reuse

Eye: Remove contact lenses, if present and easy to do. Flush with water for 15 minutes or until irritation subsides. Get medical attention.

Symptoms and effects, both acute and delayed:

Acute: Skin exposure may cause slight irritation to personnel with allergenic tendencies. Eye contact may result in transient corneal inflammation. Low order of oral toxicity.

Chronic: Prolonged or repeated skin contact may tend to remove natural oils, resulting in the development of dermatitis.

5 - FIRE-FIGHTING MEASURES

Extinguishing media:

Suitable: Foam, carbon dioxide, dry chemicals, water fog or spray.

Unsuitable: Do not use straight streams of water, as this will spread the fire.

Specific hazards and combustion products: Thermal decomposition can lead to the release of irritating gases and vapors.

Special protective equipment and precautions for fire-fighters: If near fire, cool exposed containers with cold water to prevent rupture. If a spill has not ignited, use water spray to disperse vapors. Minimize breathing fumes. Firefighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing. Treat as oil fire.

6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: All persons dealing with the spill should wear appropriate personal protective equipment. Keep others away from spill. Restrict access to area until the spill has been cleaned up.

Methods and materials for containment and cleaning up: Contain spill and transfer to suitable containers or soak up in absorbent medium. If spill enters sewer, notify proper authorities.

7 - HANDLING AND STORAGE

Precautions for safe handling: Wear proper personal protective equipment. Minimize breathing hot vapors. Avoid

contact with skin, eyes and clothing. Personnel in close vicinity to oil mists above TLV limit should wear approved breathing devices. Wash thoroughly before meals and at end of work periods. Launder or dry-clean soiled clothing before reuse.

Conditions for safe storage: Keep containers closed when not in use. Protect from freezing temperatures. Avoid

heating above 120°F for prolonged periods of time. Do not store or handle near ignition sources or strong oxidants. Empty containers may retain product residue; all

precautions apply to empty containers.

Incompatible materials: Strong oxidizing materials.

8 - EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure limits: 5 mg/m³ as oil mist in air.

Engineering controls: Good general ventilation and/or local exhaust ventilation is recommended.

Individual protection measures and personal protective equipment: Splash goggles, face shield, chemical and oil resistant gloves. Use chemical resistant apron if needed to avoid prolonged or repeated skin contact.

TLV (THRESHOLD LIMIT VALUE): 5mg/m³ as oil mist in air over an 8 hour daily exposure (ACGIH)

9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Amber Liquid **Odor:** Hydrocarbon

Odor threshold: Data currently unavailable

Product pH: 9.0 - 9.5

Freezing point: Data currently unavailable
Boiling point: Data currently unavailable
Flash point: 315°F (on base oil)

Evaporation rate: Negligible

Flammability: Information not available.

Upper/lower flammability limits: LEL: 0.9% UEL: 7.0%

Vapor pressure: < 0.01 mm Hg @ 68°F **Vapor density:** >1 (Air = 1)

Vapor density: >1 (Air = 1) Relative density: 0.92 (Water = 1)

Solubility: Emulsifiable in water and alcohols.

Partition coefficient (n-octanol/water): Information not available.

Auto-ignition temperature: Information not available.

Decomposition temperature: Information not available.

Viscositivi Information not available.

Viscosity: Information not available.

10 - STABILITY AND REACTIVITY

Chemical stability: Material is stable under normal conditions.

Possibility of hazardous reactions: Hazardous polymerization will not occur. **Conditions to avoid:** Avoid heat, sparks, open flames and other ignition sources.

Incompatible materials: Strong oxidizing agents.

Hazardous decomposition products: Material does not decompose at ambient temperatures. Decomposition products may include and are not limited to oxides of carbon and other toxic gases when exposed to combustion.

11 - TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Inhalation: Yes Ingestion: Yes Skin: Yes Eye: Yes

Potential Symptoms of exposure:

Inhalation: No information available. Ingestion: No information available.

Skin: Minimally toxic under normal use. May be mildly irritating with prolonged and/or repeated skin

contact.

Eye: Contact with eyes may cause severe irritation with possibility of injury. Injuries not expected

under normal use.

Toxicological data: TLV: 5mg/m³ as oil mist in air.

NTP, IARC or OSHA carcinogen: None of the constituents of this product have been identified as possible or

proven carcinogens by NTP, IARC, or OSHA.

12 - ECOLOGICAL INFORMATION

Ecotoxicity: Data not available.

Persistence and degradability: Data not available. Bioaccumulative potential: Data not available.

Mobility in soil: Data not available.

Other adverse effects: None known.

13 - DISPOSAL CONSIDERATIONS

Waste disposal method: Dispose of in accordance with federal, state and local regulations.

14 - TRANSPORT INFORMATION

DOT Shipping: Not regulated by the U.S. Department of Transportation as a hazardous material.

DOT Hazard class: Not Regulated. UN/NA Number: Not Regulated.

Component

15 - REGULATORY INFORMATION

Sara III (Superfund Amendment and Reauthorization Act of 1986) 40 CFR Part 372 and 40 CFR Part 355

RQ (lbs.)

TPQ (lbs.)

CAS#

Sections 302, 304 and 40 CFR Part 355 – Extremely Hazardous Substances:

NONE Sections 311, 312 and 40 CFR Part 355 – Hazard Categories: ACCUTE(IMMEDIATE HEALTH HAZARD): YES FIRE HAZARD: YES CHRONIC (DELATED HEALTH HAZARD): NO REACTIVE HAZARD: SUDDEN PRESSURE RELEASE: NO Sections 313 and 40 CFR Part 372 – Toxic Chemicals: Component % CAS# NONE

CERCLA (Comprehensive Environmental Response, Compensation and Liability Act)

Section 102 and 40 CFR Part 302 – Hazardous Substances:

 Component
 %
 RQ (lbs.)
 CAS#

 NONE

CLEAN WATER ACT

Under section 311 (b) (4) of this act, contamination of surface waters by petroleum products must be reported immediately to the National Response Center. SECTION 311 (b) (4) DOES NOT APPLY TO TOWERPRO 5212-B

California Proposition 65: None of the ingredients are listed.

TSCA (Toxic Substances Control Act): All components of this formula are listed in the TSCA inventory.

16 - OTHER INFORMATION

Preparation Date: May 5, 2015 **Revision Date:** December 21, 2021

The information appearing in this document is based upon data obtained from raw material manufacturers and/or recognized technical sources. While this information is believed to be correct, TOWER METALWORKING FLUIDS makes no representations as to its accuracy or sufficiency, usage, or the hazards connected with the use of this material. Since this product may be applied under conditions unfamiliar to us or beyond our control, we claim no responsibility for the results of its use, and users are responsible for the verification of this information under their own operation conditions to determine whether the product is suitable for their particular purposes, and these users assume all risks of their use, handling, and disposal of the product. This information relates only to the product designated above and does not relate to its use in combination with any other material in any other process.