



RUSTBEAT 699

RUSTBEAT 699 is a highly effective low viscosity rust and corrosion inhibitor that leaves a light oily film. It has been formulated to provide protection for ferrous metals during inside storage and long distance transit. **RUSTBEAT 699** has excellent water displacing and separating characteristics.

USAGE

RUSTBEAT 699 is recommended for use on cold draw bar, ground and polished bars and other steel products. It is designed to be used as received and can be applied by spraying, wiping, flooding or by submerging in a dip tank. **RUSTBEAT 699** is easy to clean in an aqueous wash with an alkaline cleaner such as **TOWERKLENE 42-A**.

PHYSICAL CHARACTERISTICS

Density	0.89 g/ml 7.4 lbs/gal
Appearance	Amber Liquid
Odor	Bland Petroleum
Type of Film	Light Oily
Viscosity	Typically 40 SUS @ 100°F
Flash Point	>230°F (COC)
Humidity Cabinet Testing	400 Hours Minimum @ 100°F and 95-100% RH
Indoor Protection	Approximately One Year

TECHNICAL SUPPORT

This is a Proprietary product. TOWER wants to assist you in evaluation and selection of suitable products. We urge you to take advantage of this service. This information sheet and TOWER's assistance, however, are not a substitute for your own testing and evaluation.