



WELD ANTI-SPATTER RP

WELD ANTI-SPATTER RP is a synthetic, non-flammable, non-toxic liquid that prevents hot spatter from sticking to work pieces and fixtures. Any spatter falling on an area treated with **WELD ANTI-SPATTER RP** will not stick and can be easily brushed away. Its ingredients are carefully selected to not cause hazardous fumes and discomfort to welders or surrounding workers. **WELD ANTI-SPATTER RP** does not contain Silicones or Ozone depleting chemicals and will not inhibit secondary operations like painting, galvanizing, or other plating processes. **WELD ANTI-SPATTER RP** can also be used as a short term rust preventive on ferrous metals stored indoors.

USAGE

WELD ANTI-SPATTER RP requires no mixing, it is used as received. Spray a light coating of the liquid on areas where spatter is a concern. It can also be sprayed into welding nozzles to prevent spatter build-up in this area. If need be, **WELD ANTI-SPATTER RP** can be removed with warm water or a mild alkaline cleaner. The product should be stored above 40° F. If frozen just return it to room temperature.

PHYSICAL CHARACTERISTICS

Appearance	Clear pale yellow liquid
Odor	Bland
Flash Point	None
Freezing Point	32° F.

BENEFITS

- **No Mixing Required**
- **No Odor**
- **Effectively Prevents Spatter From Sticking**
- **Provides Rust Protection**
- **Non-Flammable, Non-Toxic**
- **Clean Weld Through**
- **Excellent Operator Acceptance**

TECHNICAL SUPPORT

TOWER wants to assist you in evaluation and selection of suitable products. We urge you to take advantage of this service. This information sheet and **TOWER's** assistance, however, are not a substitute for your own testing and evaluation.