



RUSTBEAT 298

RUSTBEAT 298 is a specialty rust preventive compounded to displace water and water soluble lubricants while simultaneously depositing a corrosion protective film on metal surfaces. The formulation is also designed for complete separation from tube mill coolants. **RUSTBEAT 298** is formulated to meet the MIL-PRF-16173E specifications.

USAGE

RUSTBEAT 298 is a straight oil and can be applied by spray, brush, dip tank or recirculating spray methods. It is typically used when up to one year of indoor storage protection is required.

PHYSICAL CHARACTERISTICS

Density	0.79 g/ml 6.6 lbs/gal
Appearance	Dark Amber Liquid
Odor	Mild Petroleum
Flash Point (TCC)	Greater than 105°F
Film	Dry
Coverage	1200 Square Feet per Gallon
Indoor Protection	Approximately 12 months

BENEFITS

- **Displaces Water Efficiently**
- **Does Not Contaminate Tube Mill Coolants**
- **Provides Up To Twelve Months Indoor Protection**
- **Separates Completely From Water Based Coolants**

TECHNICAL SUPPORT

TOWER wants to assist you in evaluation and selection of suitable products. We urge you to take advantage of this service. This information sheet and **TOWER's** assistance, however, are not a substitute for your own testing and evaluation. 09048