



## RUSTBEAT 46-SRP

**RUSTBEAT 46-SRP** is a synthetic, biodegradable, rust preventive. It does not contain mineral oil and has no Volatile Organic Compounds (VOC's). **RUSTBEAT 46-SRP** provides excellent in-door rust protection of steel parts. **RUSTBEAT 46-SRP** dries quickly leaving a thin, dry to the touch film.

### USAGE

**RUSTBEAT 46-SRP** is rated for 3 months @ 7% mix to 12 months @ 25% mix for indoor storage of ferrous metals. It may be applied as a corrosion inhibitor by spray, wipe, or dipping methods. **RUSTBEAT 46-SRP** is easily removable with an alkaline cleaner such as **TOWERKLENE 42-A**.

### PHYSICAL CHARACTERISTICS

Appearance	Golden Liquid
Odor	Bland
Flash Point	None
Volatile Organic Compounds	None
Density	1.02 g/ml 8.5 lb/gal
pH	9.6
RI Factor	2.63 x RI = Volume %

### BENEFITS

- **Excellent Rust & Stain Protection**
- **Non-Hazardous, No Pictograms on the Label**
- **Can Weld Over the Rust Preventive Film**
- **Does NOT Contain Petroleum Oil**
- **Easy To Clean In Alkaline Cleaning Systems**
- **Dry to The Touch Film**
- **Contains No VOC's or HAP's**
- **Good Operator Acceptance**

### TECHNICAL SUPPORT

**TOWER** wants to assist you in evaluation and selection of suitable products. We urge you to take advantage of this service. This information sheet and **TOWER's** assistance, however, are not a substitute for your own testing and evaluation.

10321